

INSULATED PANELS
COLD STORE, ROOF & WALL



Head Office

P.O.Box: 115408, Plot No: 598-1106
Dubai Investment Park, Dubai
United Arab Emirates

Tel: +971 (0)4 885 9600
Email: info@emiratespanel.com



emiratespanel.com



الامارات لصناعة اللوح العازلة
Emirates Industrial Panel

TABLE OF CONTENTS

Introduction	02	CSP Heat Transmission Table	15
Production Technology	03	CSP Installation Details	16
Applications	04	EIP ROOF & WALL PANELS	20
Design & Engineering Services	05	TRP: Trapezoid Roof Panel 40/333	21
EIP PANEL FEATURES	06	TRP: Trapezoid Roof Panel 40/333 Flex	23
Surface Profiles	06	TRP: Trapezoid Roof Panel 45/150	25
Insulation Core	07	HFW: Hidden-Fix Wall (Architectural)	27
Metal Facers	08	TFW: Through-Fix Wall & Partition	29
Quality Assurance	09	SWP: Standard Wall Panel	31
Fire Shield	10	Roof & Wall Installation Details	33
EIP COLD STORE PANEL	13	DELIVERY, HANDLING & STORAGE	37
CSP Wall & Ceiling Span Guide	14	DOORS	39

INTRODUCTION

Emirates Industrial Panel (EIP) was established in 2007 in Dubai to meet the ever-growing market demand for high-quality insulated sandwich panels.

Through our state-of-the-art German continuous production line, we are able to manufacture roof & wall facade cladding, internal partitioning, and cold store panels of the highest quality.

Our panels are customizable, locally certified, FM approved, and have been used in over 55 countries worldwide.



PRODUCTION TECHNOLOGY

EIP's state-of-the-art German continuous production line has a production capacity of over 3 million square meters of panels per annum.

The production system features multiple stations, including: a profiling section, a foam application station, a special cut-to-length system, a curing zone, and an automatic stacking & packaging unit. The fully automated line requires minimum operator intervention, maximizing quality and efficiency.

The plant proudly operates using environmentally friendly blowing agents that meet international standards.



APPLICATIONS


EIP panels are used for an array of different applications in various industries.

From pharmaceutical centers to vertical farms, EIP panels are designed for temperature-sensitive applications that require optimal hygiene standards and safety.

Our panels are suitably made for different construction designs such as:

- Single-external-box
- Box-in-a-box
- Rack-supported cladding systems

- ✓ Distribution Centers
- ✓ Cold Stores
- ✓ Fruit & Vegetable Storage
- ✓ Pharmaceuticals
- ✓ Leisure & Recreation
- ✓ Fish & Meat Processing
- ✓ Vertical Farming
- ✓ Dairy Processing Plants






At EIP, our experts are prepared to provide you with detailed engineering and technical advice at any stage of your project.

Some of the services that EIP provides are:




- ✓ Panel estimation based on project drawings
- ✓ Preparation of shop drawings, including detail solutions
- ✓ Final BOQ that includes panels, flashings & accessories
- ✓ Preparation of drawings to guide the installation team
- ✓ Site supervisor to guide the installation team
- ✓ Assistance in selecting an EIP-certified contractor for the installation of sandwich panels

All or a combination of the above services are available upon assessing the requirement of each project.

Internal & external facers of EIP panels have a standard Low Rib profile on both sides, unless specified otherwise.





AVAILABLE UPON REQUEST



SURFACE PROFILES - ROOF & WALL

TRP 40/333 and 45/150 panels have 40/333 corrugated and 45/150 corrugated profiles on the external side respectively, and have a Low Rib profile on the internal side.

HFW and TFW panels have Low Rib profiles as the standard on both sides.




INSULATION CORE

The core of an EIP panel is rigid insulated foam, available as:

- ✓ FM Approved, fire resistant Polyisocyanurate (PIR) foam
- ✓ Flame Reaction (PUR) B1 class
- ✓ Flame Reaction (PUR or PIR) B2 class
- ✓ Polyurethane (PUR) B3 class

The blowing agent used in EIP panels is environmentally-friendly pentane gas, with:

- ✓ Zero Ozone Depletion Potential (OPD)
- ✓ Low Global Warming Potential (GWP)
- ✓ Zero CFC and HCFC



Closed Cell content
>%90

Density
 $40 \pm 3 \text{ kg/m}^3$

Thermal Conductivity
 $\lambda_{\text{PUR}} = 0.023 \text{ W/mk}^1$
 $\lambda_{\text{PIR}} = 0.021 \text{ W/mk}^1$

METAL FACERS

The standard substrate for internal and external facers is pre-painted & hot-dip galvanized steel.

Thickness	0.50 mm
Steel Grade	DX51D
Top Coat	Polyester, PES, 25 microns thick
Colour	RAL 9002 Off-white
Surface Protection	Polyethylene (PE) film

Variations are possible in the surface material specifications to suite a wide range of specialized applications:

Thickness Options	0.40 mm to 0.80 mm
Substrate Options	Aluzinc-coated steel, Stainless steel (SS 304 or 316), Aluminium
Colour Options	Any colour from the RAL catalogue

TOP COAT OPTIONS

HDP (High Durable Polyester) coating is suitable for increased resistance against corrosion and harsh cleaning agents.

PVDF (Polyvinylidene Difluoride) coating is effective for external applications where higher resistance against corrosion, colour fading, and harsh environment conditions is required.


Plastisol coating is highly chemical resistant. This tough coating is suitable in internal applications for non-contact level food safety.

Food Safe coating has anti-microbial properties, which is ideal in internal applications such as kitchens for contact-level food safety.

EIP PANEL BENEFITS

- ✓ LIGHT WEIGHT
 - ✓ HIGH RIGIDITY
 - ✓ SUPERIOR INSULATION
 - ✓ FIBER-FREE CORE
 - ✓ CLOSED CELL FOAM
- ✓ EFFECTIVE FIRE RESISTANCE
 - ✓ RESISTANCE TO ADVERSE WEATHER
 - ✓ AIR-TIGHT, FIRE RATED JOINT
 - ✓ HYGIENIC SURFACE (AS PER HACCP)
 - ✓ ZERO ODP, LOW GWP

STEEL FACER DETAILS



QUALITY ASSURANCE

EIP is committed to providing clients with high-quality products and services.

Our team of experts operate a well-equipped laboratory to manage our effective **Quality Management System**. They use advanced technology to ensure our products are continually tested and meticulously reviewed. Numerous checks are routinely conducted on incoming raw materials, unfinished panels, and final products.

EIP's Quality System meets the requirements of ISO 9001:2008, and is regularly audited by four bodies:

- Peers Quality Assurance Limited
- Dubai Central Laboratories
- FM Approvals
- Emirates Safety Laboratory



EIP FIRE SHIELD

Reliable fire resistance is necessary in the developing world of construction materials. Standard polyurethane and polystyrene insulated panels are vastly inefficient against fire, unlike the truly fire-resistant sandwich panels that utilize EIP Fire Shield technology.

PIR Insulation Core

EIP Fire Shield panels contain a high grade polyisocyanurate (PIR) insulation core, which provides superior fire-resistance when compared to most alternative standard insulation materials. PIR is a thermosetting material, which means that it will permanently become hard and rigid when heated, and will not melt or drip when exposed to fire. The foam core forms a strong carbonaceous char, creating a protective layer from flames. With these properties, EIP Fire Shield PIR panels have been proven to help reduce the risk of critical building loss.

Double Tongue & Groove Fire-Rated Joint

A specially-designed joint protects the core from flame ingress. This enables the panel to maintain its structural integrity when exposed to fire.

When exposed to a real fire situation, EIP Fire Shield Panels:

- ✓ Do not contribute to the fire or act as a fuel to it
- ✓ Do not spread flames on their surface
- ✓ Give off minimal smoke
- ✓ Preserve their insulation properties¹
- ✓ Preserve their structural integrity¹
- ✓ Self-extinguish when the fire source is removed



CERTIFICATIONS

EIP Fire Shield panels have received FM Approval as **Class 1 insulated panels with no height restriction** in accordance with FM Approvals standards 4880, 4881, 4882, and 4471.

FM 4880	Overall Fire Performance of Insulated Panels
FM 4881	External Wall Panels
FM 4882	Suitability for Smoke-Sensitive Occupancies
FM 4471	Roof Panels
EN 13501-1	Reaction-to-Fire Classification of Non-Load Bearing Walls
EN 13501-2	Fire Resistance of Non-Load Bearing Elements
ASTM E84 (NFPA 255)	Surface Burning Characteristics of Building Materials
NFPA 285	Fire Propagation Characteristics of Exterior Non-Load Bearing Walls
ASTM E108	Standard Test Methods for Fire Tests of Roof Coverings
ASTM D1929	Standard Test Method for Determining Ignition Temperature of Plastics
BS 22 476	Fire Resistance of Non-Load Bearing Elements

¹ As per EN 13501-2 at a certain time limit



COLD STORE PANELS



EIP CSP: COLD STORE PANEL

EIP's Cold Store Panel (CSP) is perfect for walls, ceilings, partitions, and roof applications with waterproofing; offering superior insulation, durability, and easy installation for temperature-controlled environments.



Thermal Performance & Weight								
t: Core Thickness (mm)	55	80	100	120	140	150	170	200
Weight (kg/m ²) ¹	10.40	11.40	12.20	13.00	13.80	14.20	15.00	16.20
U value - PIR (W/m ² K) ²	0.38	0.26	0.21	0.17	0.15	0.14	0.12	0.10


¹ Based on 0.50mm thick outer facers
² As per foam laboratory values
* Consult EIP's technical team for updated values with different foam systems.

CSP JOINT SYSTEM

A double tongue-and-groove edge ensures that the panels precisely interlock with utmost ease.

This eliminates the risk of thermal bridging and provides an air-tight joint between the panels.


The extended steel edges within the joint system provide additional strength and protection against fire by prolonging the amount of time flames take to reach the panel's core.



COLD STORE PANEL WALL & CEILING SPAN GUIDE

Panel lengths can vary from 2000mm to 18000mm.
This span table is based on panels with the standard 0.50mm steel thickness for internal and external facers.

While using CSP panels as self-standing partition panels, the following wall and ceiling span guide will show the maximum panel lengths for different thicknesses.



* Span table is based on panels with 0.50mm thick steel internal and external facers
* Wall panel length goes up to 18000mm with additional support

COLD STORE PANEL HEAT TRANSMISSION TABLE

Panel Thickness (mm)	55	80	100	120	140	150	170	200
Temperature Differential (TD)								
10°C	3.78	2.60	2.08	1.73	1.49	1.39	1.22	1.04
15°C	5.67	3.90	3.12	2.60	2.23	2.08	1.84	1.56
20°C	7.56	5.20	4.16	3.47	2.97	2.77	2.45	2.08
25°C	9.45	6.50	5.20	4.33	3.71	3.47	3.06	2.60
30°C	11.35	7.80	6.24	5.20	4.46	4.16	3.67	3.12
35°C	13.24	9.10	7.28	6.07	5.20	4.85	4.28	3.64
40°C	15.13	10.40	8.32	6.93	5.94	5.55	4.89	4.16
45°C	17.02	11.70	9.36	7.80	6.69	6.24	5.51	4.68
50°C	18.91	13.00	10.40	8.67	7.43	6.93	6.12	5.20
55°C	20.80	14.30	11.44	9.53	8.17	7.63	6.73	5.72
60°C	22.69	15.60	12.48	10.40	8.91	8.32	7.34	6.24
65°C	24.58	16.90	13.52	11.27	9.66	9.01	7.95	6.76
70°C	26.47	18.20	14.56	12.13	10.40	9.71	8.56	7.28
75°C	28.36	19.50	15.60	13.00	11.14	10.40	9.18	7.80
80°C	30.25	20.80	16.64	13.87	11.89	11.09	9.79	8.32
85°C	32.15	22.10	17.68	14.73	12.63	11.79	10.40	8.84
Lambda Value = 0.0208 W/mK Minimum value for heat gain in a coldstore = 10 W/m² TD = Temperature difference between inside and outside of coldstore.								


COLD STORE PANEL INSTALLATION DETAILS



- 01. Wall - Floor Detail
- 02. Partition Wall - Floor Detail
- 03. Wall - Ceiling Detail
- 04. Partition Wall - Ceiling Detail
- 05. Ceiling Mid-Suspension Detail
- 06. Ceiling T-Suspension Detail
- 07. Corridor Ceiling - Wall Detail
- 08. Wall Corner Detail


COLD STORE PANEL INSTALLATION DETAILS

01 Wall - Floor Detail




- | | |
|--------------------------------|-----------------------|
| 1 Wall Panel | 5 Vapour Barrier |
| 2 Concrete Upstand | 6 Floor Heater Cables |
| 3 Concrete Floor | 7 Spray Foam |
| 4 2 Layers of Floor Insulation | 8 Floor Angle |

02 Partition Wall - Floor Detail




- | | |
|--------------------------------|-----------------------|
| 1 Partition Panel | 5 Vapour Barrier |
| 2 Concrete Upstand | 6 Floor Heater Cables |
| 3 Concrete Floor | 7 Spray Foam |
| 4 2 Layers of Floor Insulation | 8 Floor Angle |

05 Ceiling Mid - Suspension Detail




- | | |
|----------------------|-----------------|
| 1 Purlin | 5 Ceiling Panel |
| 2 Angle Support | |
| 3 Threaded Rod | |
| 4 PVC Threaded Screw | |

06 Ceiling T - Suspension Detail




- | | |
|-----------------|--------------------------|
| 1 Rafter | 5 Flat Flashing |
| 2 Beam Clamp | 6 Spray Foam |
| 3 Angle Support | 7 Aluminium T-Suspension |
| 4 Threaded Rod | 8 Ceiling Panel |

03 Wall - Ceiling Detail




- | | |
|-------------------|--------------------------|
| 1 Ceiling Panel | 5 Aluminium Corner Angle |
| 2 Corner Flashing | |
| 3 Wall Panel | |
| 4 Spray Foam | |

04 Partition Wall - Ceiling Detail




- | | |
|-------------------|--------------------------|
| 1 Ceiling Panel | 5 Aluminium Corner Angle |
| 2 Flat Flashing | |
| 3 Partition Panel | |
| 4 Spray Foam | |

07 Corridor Ceiling - Wall Detail



- | | |
|-------------------|--------------------------|
| 1 Ceiling Panel | 5 Ceiling Panel |
| 2 Corner Flashing | 6 Spray Foam |
| 3 Wall Panel | 7 Aluminium Corner Angle |
| 4 Corner Flashing | 8 Aluminium Corner Angle |

08 Wall - Wall Corner Detail



- | | |
|-------------------|--------------------------|
| 1 Wall Panel | 5 Aluminium Corner Angle |
| 2 Corner Flashing | |
| 3 Wall Panel | |
| 4 Spray Foam | |




EIP TRP: TRAPEZOID ROOF PANEL 40/333

The TRP 40/333 is a trapezoid formed roof panel, through-fixed on the side-lap joints. The name '40/333' indicates the rib height (40mm) and valley width (333mm) of this panel.

40mm high ribs provide improved strength and water-resistance against turbulent weather conditions. This is an all-rounder roof cladding suitable for use in all buildings with roof slopes as low as 2.85° (5.0%)¹.

Note that all EIP TRP panels can be installed as roof or wall fixtures.



TRP 40/333's minimum length is 2000mm and maximum length is 18000mm.

Thermal Performance & Weight						
t: Core Thickness (mm)	40	50	60	75	100	150
Weight - Steel (kg/m²) ²	10.30	10.70	11.10	11.70	12.70	14.70
Weight - Aluminum (kg/m²) ³	5.40	5.80	6.20	6.80	7.80	9.80
U value - PIR (W/m²K) ⁴	0.43	0.36	0.31	0.25	0.19	0.13
U value - PUR (W/m²K) ⁴	0.47	0.40	0.34	0.28	0.21	0.14

¹ Contact EIP's technical team for assistance with selecting the correct design for your required slope.
² Based on 0.50mm thick outer facers
³ Based on 0.70mm thick outer facers
⁴ As per foam laboratory values
* Consult EIP's technical team for improved values with different foam systems.

EIP TRP: TRAPEZOID ROOF PANEL 40/333




EIP TRP: TRAPEZOID ROOF PANEL 40/333 FLEX

The TRP 40/333 Flex is a lighter variant of the TRP 40/333, with the same trapezoid form but featuring aluminium foil as the inner sheet of the panel. This panel is through-fixed on the side-lap joints.

This is an all-rounder roof cladding suitable for use in all buildings with roof slopes not less than 5° (8.75%)¹.

It is a functional and economic option to clad the roofs of buildings effectively.

EIP TRP: TRAPEZOID ROOF PANEL 40/333 FLEX



TRP 40/333 Flex's minimum length is 2000mm and maximum length is 10000mm.

Thermal Performance & Weight		
t: Core Thickness (mm)	50	75
Weight - Steel (kg/m²) ²	6.70	7.70
Weight - Aluminum (kg/m²) ³	4.40	5.40
U value - PIR (W/m²K) ⁴	0.36	0.25
U value - PUR (W/m²K) ⁴	0.40	0.28

¹ Contact EIP's technical team for assistance with selecting the correct design for your required slope.

² Based on 0.50mm thick outer facers

³ Based on 0.70mm thick outer facers

⁴ As per foam laboratory values



* Consult EIP's technical team for improved values with different foam systems.



EIP TRP: TRAPEZOID ROOF PANEL 45/150

The TRP 45/150 is a trapezoid formed roof panel, through-fixed on the side-lap joints. The name '45/150' indicates the rib height (45mm) and valley width (150mm) of this panel. This panel is suitable for use in all buildings with roof slopes as low as 2.85° (5.0%)¹.

The height and number of ribs on this roof panel provide superior strength, longer distance spanning capability, and effective water resistance. This improved strength model is designed to withstand demanding conditions.



TRP 45/150's minimum length is 2000mm and maximum length is 18000mm.

Thermal Performance & Weight					
t: Core Thickness (mm)	45	50	70	95	145
Weight - Steel (kg/m²) ²	11.30	11.50	12.30	13.30	15.30
Weight - Aluminum (kg/m²) ³	6.00	6.20	7.00	8.00	10.00
U value - PIR (W/m²K) ⁴	0.38	0.35	0.26	0.20	0.13
U value - PUR (W/m²K) ⁴	0.42	0.38	0.29	0.22	0.14

¹ Contact EIP's technical team for assistance with selecting the correct design for your required slope.

² Based on 0.50mm thick outer facers

³ Based on 0.70mm thick outer facers and 0.50mm thick inner faces

⁴ As per foam laboratory values

* Consult EIP's technical team for improved values with different foam systems.


EIP TRP: TRAPEZOID ROOF PANEL 45/150



EIP HFW: HIDDEN-FIX WALL (ARCHITECTURAL)

The HFW is an architectural wall panel with a hidden-fix joint system. This system conceals the fasteners used to install the panels, providing a smooth, aesthetic look to the building's façade. It can be installed horizontally or vertically on any building with positive internal temperatures.

The top choice of architects, HFW panels can easily be cut and modified to satisfy different needs without sacrificing the beauty of a façade.



HFW panel's minimum length is 2000mm and maximum length is 18000mm. Care must be shown while selecting longer lengths for HFW panels. Mishandling during unloading and installation can cause damage. EIP's technical department will be available to provide additional guidance.

Thermal Performance & Weight					
t: Core Thickness (mm)	50	75	100	120	150
Weight - Steel (kg/m²) ¹	10.30	11.60	12.60	12.40	14.90
Weight - Aluminum (kg/m²) ²	5.50	6.60	7.60	8.00	10.40
U value - PIR (W/m²K) ³	0.42	0.28	0.21	0.17	0.14
U value - PUR (W/m²K) ³	0.46	0.30	0.23	0.19	0.15

¹ Based on 0.50mm thick facers
² Based on 0.70mm thick outer facers and 0.50mm thick inner facers
³ As per foam laboratory values
* Consult EIP's technical team for improved values with different foam systems.


EIP HFW: HIDDEN-FIX WALL (ARCHITECTURAL)



EIP TFW: THROUGH-FIX WALL & PARTITION

The TFW is a double tongue-and-groove joint wall panel. This standard panel is through-fixed onto structures. It can be installed horizontally or vertically on any type of building.

Thanks to their design, EIP's TFW panels can be used as self-standing internal partition walls and suspended ceilings.



TFW panel's minimum length is 2000mm and maximum length is 18000mm.
Care must be shown while selecting longer lengths for TFW panels. Mishandling during unloading and installation can cause damage. EIP's technical department will be available to provide additional guidance.

Thermal Performance & Weight								
t: Core Thickness (mm)	55	80	100	120	140	150	170	200
Weight - Steel (kg/m²) ¹	10.40	11.40	12.20	13.00	13.80	14.20	15.00	16.20
Weight - Aluminum (kg/m²) ²	5.60	6.60	7.40	8.20	9.00	9.40	10.20	11.40
U value - PIR (W/m²K) ³	0.38	0.26	0.21	0.17	0.15	0.14	0.12	0.10
U value - PUR (W/m²K) ³	0.41	0.28	0.23	0.19	0.16	0.15	0.13	0.11

¹ Based on 0.50mm thick facers
² Based on 0.70mm thick outer facers and 0.50mm thick inner facers
³ As per foam laboratory values
* Consult EIP's technical team for improved values with different foam systems.

EIP TFW: THROUGH-FIX WALL & PARTITION




EIP SWP: STANDARD WALL PANEL

The SWP has an economic design for low-rise buildings.

This panel features a slip-joint and is through-fixed onto a structure.

It can be installed horizontally or vertically, and is predominantly used in agricultural or modular prefabricated buildings.



SWP's minimum length is 2000mm and maximum length is 12000mm.

Thermal Performance & Weight		
t: Core Thickness (mm)	40	50
Weight - Steel (kg/m²) ¹	10.00	10.40
Weight - Aluminum (kg/m²) ²	5.70	6.10
U value - PIR (W/m²K) ³	0.53	0.42
U value - PUR (W/m²K) ³	0.58	0.46

¹ Based on 0.50mm thick facers

² Based on 0.70mm thick outer facers and 0.50mm thick inner facers

³ As per foam laboratory values

* Consult EIP's technical team for improved values with different foam systems.


EIP SWP: STANDARD WALL PANEL






- 01. Roof Ridge Detail
- 02. Roof Panel Overlap Detail
- 03. Skylight Detail
- 04. Insulated Valley Gutter Detail
- 05. Insulated Eave Gutter Detail
- 06. Side Wall Detail
- 07. Drip Flashing Detail
- 08. Joint Flashing Detail
- 09. Opening Detail
- 10. Gable Detail
- 11. Insulated Curved Eave Detail - 1
- 12. Insulated Curved Eave Detail - 2

01 Roof Ridge Detail




- 1 Self-Drilling Screw
- 2 Butyl Tape
- 3 Purlin
- 4 Outer Ridge Flashing
- 5 Inner Ridge Flashing
- 6 Roof Panel

02 Roof Panel Overlap Detail




- 1 Self-Drilling Screw
- 2 Butyl Tape
- 3 Roof Panel
- 4 GI Angle
- 5 Purlin

03 Skylight Detail




- 1 Self-Drilling Screw
- 2 Butyl Tape
- 3 Skylight
- 4 GI Angle
- 5 Purlin
- 6 Roof Panel

04 Insulated Valley Gutter




- 1 Self-Drilling Screw
- 2 Roof Panel
- 3 Filler Block
- 4 Purlin
- 5 Insulated Valley Gutter
- 6 Foam Enclosure Flashing

05 Insulated Eave Gutter Detail




- | | |
|-------------------------|---------------------------|
| 1 Cap Flashing | 7 Purlin |
| 2 Fiber Insulation | 8 Filler Block |
| 3 Wall Panel | 9 Foam Enclosure Flashing |
| 4 Backer Panel | 10 Self-Drilling Screw |
| 5 Drip Flashing | 11 Roof Panel |
| 6 Insulated Eave Gutter | |

06 Side Wall Detail




- | | |
|-------------------------|----------|
| 1 Concrete Parapet Wall | 7 Purlin |
| 2 Drip Flashing | |
| 3 Expansion Bolt | |
| 4 Self-Drilling Screw | |
| 5 Side Wall Flashing | |
| 6 Roof Panel | |

09 Opening Detail




- | |
|--------------------|
| 1 Drip Flashing |
| 2 Opening Flashing |
| 3 Wall Panel |
| 4 Purlin |

10 Gable Detail




- | | |
|------------------|-----------------------|
| 1 Gable Flashing | 4 Self-Drilling Screw |
| 2 Roof Panel | 5 GI Angle |
| 3 Purlin | 6 Wall Panel |

07 Drip Flashing Detail




- | | |
|-----------------------|-----------------|
| 1 Self-Drilling Screw | 4 Concrete Wall |
| 2 Drip Flashing | 5 Purlin |
| 3 GI Angle | 6 Wall Panel |

08 Joint Flashing Detail




- | |
|-----------------------|
| 1 Self-Drilling Screw |
| 2 Joint Flashing |
| 3 Wall Panel |
| 4 GI Angle |
| 5 Purlin |

11 Insulated Curved Eave Detail - 1



- | | |
|---------------------------|-------------------------|
| 1 Self-Drilling Screw | 6 Purlin |
| 2 Roof Panel | 7 Fiber Insulation |
| 3 Butyl Tape | 8 Curved Eave Sheetting |
| 4 Foam Enclosure Flashing | 9 Drip Flashing |
| 5 GI Angle | 10 Wall Panel |

12 Insulated Curved Eave Detail - 2



- | | |
|---------------------------|--------------------|
| 1 Butyl Tape | 6 Wall Panel |
| 2 Foam Enclosure Flashing | 7 Fiber insulation |
| 3 Roof Panel | 8 GI Angle |
| 4 Self-Drilling Screw | 9 Purlin |
| 5 Curved Eave Sheetting | |

DELIVERY, HANDLING & STORAGE

EIP panels will arrive at your premises packed in bundles. Each bundle will contain a number of panels wrapped together with transparent polyethylene (PE) film. The bottom of these panels will also be supported by multiple polystyrene blocks. Each individual panel will have protective film on its surface to prevent scratches.

Every transport vehicle can take four rows of EIP panels, even with different panel counts in each bundle for different panel types. Land and sea freight vehicle capacities differ due to the vehicle dimensions.

Please contact EIP to get more details about the number of panels per bundle to expect based on your project's specifications.



Special Packaging


Certain destinations may require special packing. Upon request, we can create reinforced packing using extra wrapping, timber elements, or crates. Additional charges will apply.



Handling

Panel stacks are carefully loaded & strapped at our factory to ensure clients receive their panels in optimum condition. It is critical to correctly handle the panels while unloading or moving.

All EIP panel bundles have instruction sheets taped on them to outline the handling, transportation, and storage guidelines that should be followed.



Unloading at Site

Extreme care is advised when unloading the panels at site. A forklift or a crane equipped with a spreader beam must be used to avoid pressure on the panel edges, which can damage the joints and warp the panel surface.



Storage

Panels should be stored in a shaded area, on a clean & flat surface, with no more than two bundles on top of each other. If no covered area is available, panels should be covered with a cloth material to protect the panels from dust and rain, but also allow for air circulation underneath the cover.

Protective Film

Avoid prolonged storage times. Panels should be installed soon after they are received. Remove the surface protection film after installation.

If the panels are not installed immediately and are kept in a packed condition for an extended period, the protective foil may affect the surface quality of the panels. It should be removed with care as soon as possible. Please contact EIP for additional instructions in case you face this.



DELIVERY, HANDLING & STORAGE



DOORS

A range of doors are offered by EIP to suit a wide variety of applications for industrial & commercial projects:

- ✓ Hinged doors
- ✓ Manual horizontal sliding doors
- ✓ Automatic horizontal sliding doors
- ✓ Automatic vertical sliding doors
- ✓ Rapid access doors for chiller & freezer rooms

Door features:

- Off-white RAL 9002 door leaves as standard. Other RAL colours are available upon request.
- An internal safety release for added security.
- Door and floor heating for low-temperature applications.
- A range of thicknesses.

Stainless Steel (S.S.) hinged & sliding doors are available upon request.



CRAFTED FOR **BEAUTY**.
BUILT FOR **PERFORMANCE**.

